

An Improved Optimization Model of Multi-layer Network in Wireless Networks

Shuaili WANG

Hunan City University, Yiyang, 413000, CHINA

Abstract: In order to solve the problems of multi-layer network energy consumption, for the multi-layer network with an IP layer, TDM layer and optical layers 3-layer structure, ITO model is proposed in this paper. The modules sleeping of multi-granularity, traffic multistage grooming and bypass, the route of energy aware and varieties of energy-saving were discussed in the model. According to the specification parameters of actual network equipment to explore how different combinations of network layer, dynamic power dissipation dynamic power of network equipment and modular structure impact on energy optimization of multi-layer network by corresponding experiments. Experimental results show that: The power consumption of the network can effectively be reduced by using the model in this article.

Keywords: Cable Network; Energy-Saving Mechanisms; Optical Fiber Link; Node

1. Introduction

Due to the rapid growth of demand for network services, the system number and size which network services provide increase explosively, and also the power consumption of network service system is increasing rapidly. The increase of network service system power consumption not only increases the system operation costs, but also restricts the improvement of system performance; meanwhile produce large amounts of carbon emissions. Whether from an environmental point of view or economic point of view, energy control of network service system is becoming an important factor in system design increasingly.

Wired network energy consumption begun to be valued by people until Gupta and Singh's work, since then, there has been a lot of energy-saving research on wired networks. Bianzino A P and others summarized the wired network energy-saving research works of recent years.

When the wired network was originally designed and deployed without considering energy optimization goals, and more serious is one of two design criteria, over provisioning (over provisioning) and redundancy (redundancy) completely agree with the goal of energy consumption optimizing. The basic idea of excess configuration is that: due to the lack of QoS guarantee mechanism in Internet system configuration, in order to guarantee, it is usually configured according to the system peak load, but when the system load is low, the service capacity is remaining, it means that there is energy waste. The basic idea of redundancy is: In order to protect the system flexibility and fault tolerance, for critical system components, multiple components were deployed to deal with emergency situations. These two design criteria resulted in tremendous waste of network resources and unnecessary

energy consumption, with the skyrocketing of network size and network applications, more and more researchers design different techniques and algorithms to overcome the defects of these two designs criteria.

Internet can be roughly divided into the core network and various types of access networks, the network service system connected to the Internet through the access network to provide services. The access networks and the core network this infrastructure include many network devices and communication protocols, to a large extent, this network devices and communication protocols determines the energy consumption of the network layer. Core network consists of multiple network layers, saving research of the core network can also be divided into the energy-saving research study for a single and for multiple network layer. Power of the core network is mainly from IP layer, and therefore, lots of work is committed to reducing the power consumption of the IP layer. Energy saving method of IP layer mainly includes traffic merging and traffic distribution. The main idea of the traffic combined approach is: By adjusting the business route and converging the traffic in the network to get as much link or node as possible is idle and then make idle link or node goes to sleep (or low power consumption state) to reduce energy consumption. Traffic merging problem can be formalized and modeled to a mathematical programming problems, such as mixed integer linear programming (Mixed Integer Linear Programming, MILP) problem and integer linear programming (Integer Linear Programming, ILP) problem. These problems are usually NP-hard problem, and therefore it needs to be designed the appropriate heuristic to solve, such as Lee S of LR & HS algorithm. The main idea of traffic distribution method is: That is assumed that link has a variety of work

rate and corresponding with varieties of power, service routing is used to allocate traffic for each link and make links work in best rate mode, so that the power consumption of the network is Min. Jian T formalizes this problem as a MILP problem and designs a greedy algorithm to solve it. In addition, since the core network aggregates the traffic of the edge networks, the node is difficult to be completely idle, based on Floyd-Warshall algorithm, Cianfrani A proposed a routing Standby algorithm to introduce Standby mode for the router, and the router is shifted to Standby state to save power by adjusting the business route.

Energy-saving research of the multi-layer network aspects focused IOver WDM network, the main idea is to use the higher energy efficiency of optical switching transmission technology, through traffic grooming and bypass technology to make the traffic switch transmit to the lower WDM as possible then reduce traffic at the IP layer to decrease network power consumption. For the problem of the energy-efficient design or energy optimization of IP over WDM networks involving IP layer routing and virtual topology design problem, WDM layer routing and wavelength assignment problems and the physical topology design and regenerator placement problem in WDM layer. These problems can be formalized and modeled as MILP problem or ILP problems and to minimize the function of the network power consumption as the objective. TDM technology has the capabilities of transportation management and maintenance which WDM technology is not able to match, in the current core networks, SONET / SDH and OTN such as TDM technologies is still widely used, but the research on IP over TDM over WDM network power-saving is less. Huang S used the formalization that based on streams and interfaces to make power consumption modeling respectively on the node of IP over TDM over WDM networks, but the experiment case network is a static network, it is similar to single IP network routing problems that IP layer and the TDM layer topology are pre-configured and can not be changed. Katib I's work is similar to ours, the author has established a network power optimization model for IP / MPLS over OTN / WDM network and candidate path were used to achieve the routing of IP / MPLS layer, OTN layer and WDM layer, while it lacks the validation of experiments on model.

2. Network Model and Energy-saving Mechanisms

2.1. Network model

Multilayer network model in this paper is composed of 3 network layers: the IP layer, TDM layer and optical layer (see Figure 1). Each node in multi-layer network is usually constituted by a group of network devices, including

the IP device, TDM device and optical network equipment. The nodes connected by the fiber optic link, network device in the junction is connected through the physical line (represented in Figure 1 by the solid line). There is no direct physical link between network nodes in TDM and IP layers, the virtual path provided by the underlying network is used (like optical paths optical layer provided and TDM and the circuit TDM-layer provided) to establish their own logical link (indicated by dashed lines in Figure 1). Each network layer link collection is generally different (see Figure 1), each network node of the network layer need not set the same, the upper network node set is a subset of the set of lower layer network nodes.




Figure 1. IOver TDM over WDM network schematic diagram

Currently, a modular structure is typically used in the core network equipment the network devices are designed to be composed of machine frame and module card. According to the actual networking requirements, the necessary network equipment chassis is set up by adding the appropriate module card.

The modular design allows flexibility and scalability of network devices can be enhanced to achieve the expansion and upgrade of individual network devices by adding or replacing the module card. In addition, you can also break the capacity of a single device limitation through multi-chassis cluster approach and meet processing demands of massive business.

2.2. Energy consumption analysis

It is assumed in this article that: 1) the used MAC protocol in the sensor network is based on the CSMA transport mechanism; 2) network nodes does not moved after deployment; 3) sensor nodes have the same initial energy after dispensing; 4) sensor nodes have the same transmission radius; 5) the network lifetime is defined as the network time which first network node energy depleted.

When a node 1bit data transmitted, the transmission energy $E_{tx} = E_{ele} + E_{amp}$. Wherein E_{ele} represents the consumed energy of non-energy emitting device (frequency synthesizers, mixers, filters, etc.), η_{amp} is the

energy the transmitting device which consumed, the value is: $E_{amp} = \frac{\beta R^\gamma}{\eta_{amp}}$

Where β is the constant that related to the hardware, R is the node transmission radius, γ is the path attenuation factor, η_{amp} for the transmitter magnification. So when a network packet length is L , the energy that the node single-hop transmission consumed can be expressed as follows:

$$E_{thop} = L(E_{tx} + E_{rx}) = L(E_{ele} + \frac{\beta R^\gamma}{\eta_{amp}} + E_{rx}) \quad (1)$$




Figure 2. CSMA transmission mechanisms

Wherein, E_{rx} is the energy when node receives the energy consumption per bit.

The energy consumption of transmitted data based on CSMA mechanism is not sure each time; it is related to the number of the number of events triggered in the network and competitive transport nodes at this time. According to this paper, packet is successfully transmitted the expected energy ECSMA to measure the energy consumption of data packet transmission.

There are four sensor nodes state assumed in CSMA mechanisms: 1) idle state I; 2) An active state (carrier transmission detection); 3) T transmission status; 4) B retreat state. State transition is shown in Figure 2.

When the node is between the slot time 1 and the NAV (network allocation value), a slot time is picked in the equal probability at random, the probability of node selecting slot time r $P(r) = 1 / NAV$. According to CSMA transport mechanism, when N nodes simultaneously compete for the channel, the probability that the node successfully transmits data in slot time r is:

$$P_{success}(r) = C_N^1 P(r) \left[1 - \sum_{i=1}^r P(i) \right]^{N-1} \quad (2)$$

Correspondingly, the probability of the node selecting the slot time r but need back off:

$$P_{busy}(r) = 1 - P_{success}(r) \quad (3)$$

Thus, the probability when nodes choose different slot times and transmit successfully is $P_{success}$, the probability that it need back off is P_{busy} :

$$P_{success} = \sum_{r=1}^{NAV} P_{success}(r), P_{busy} = 1 - P_{success} \quad (4)$$

It is assume that node tried k times data transmission, and it transferred successfully last time, then the probability is:

$$P(X = K) = P_{success} P_{busy}^{k-1} \quad (5)$$

From this formula, the expected number of total transmission times during the process of this transmission is $\frac{1}{P_{success}}$. Therefore, the expected value of the total energy consumption is:

$$E_{CSMA} = E_{thop} + (1 / P_{success} - 1)E_{busy} \quad (6)$$

3. ITO Model

If the energy is seen as a system resource, then the management and control of energy consumption can be attributed to the configuration and management of resources, while the allocation of resources will need to be based on business requirements. Therefore, under the network environment, the network energy consumption can be reduced through the control of the network traffic flow and the configuration and management methods of network resources. Here the power consumption optimization problem of multilayer network which is composed of IP layer, TDM layer and optical layers is modeled, and this optimization model named ITO (IP-TDM-Optical) model. ITO model achieved the collaboration between network traffic control and network resource allocation and management, by routing methods to rationally allocate traffic between multiple network layers and in internal network-layer, according to the arrival of the traffic load, network equipment reasonably configure and manage network resources, transfer the idle module into sleep mode in order to reduce network energy consumption. ITO model is based on network flow programming theory, the multi-layer structure of the core network and the modular nature of network devices are considered, and then transformed into a linear variety streaming programming problem and become MILP problem finally.

Sensor networks can generally be described as a connected graph $G(V, A)$. Wherein the sensor node set $V = R \cup S \cup T$, R is the data source sensor node set, S to Sink node set, T is a collection of data relay node (this kind of allocation method only represents the functional division when the data is transmitting, in large-scale wireless sensor networks, other nodes except Sink nodes are likely to be data acquisition node or relay node).

Fig 3 the set of the sensor data acquisition node is assumed that $R = \{K, D\}$, the relay node is $T = \{B, C, E, F, G, H\}$ and Sink nodes $S = \{I, F\}$. When a node K collected data and requested to send to the node I , it can choose the path $K-B-D-G-I$, $K-B-E-G-I$, $K-C-F-H-I$, $K-B-D-E-G-I$ and $K-B-D-G-I$, $K-B-E-G-I$, $K-C-F-H-I$, $K-B-D-E-G-I$ this five road. When node D collected data and transmit to node F , there is only a unique path $D-E-F$.




Figure 3. Connection diagram of example network

Considering the computing power and transmission characteristics of sensor nodes in wireless sensor networks, the path cumulative power consumption routing selection mechanism is relatively simple, the route judge of the relay node is completed by the following steps: 1) calculate the size of alternative paths cumulative energy consumption of each path; 2) the packet is forwarded to the minimum cumulative energy path; 3) update the cumulative transmission power consumption in the path for each arc.

3.1. Analysis

3.1.1. Network layer and multi-layer network power consumption

By adding new routing constraints for each network layer in multi-layer network and the exchange ability of the network layer is forbidden to study each network layer and the role of network layer combinations on the network energy optimization. In addition, it enables business needs of the network layer transmission via single-hop path that the network layer switching capabilities is forbidden, the business will bypass in the underlying network by reducing the network layer traffic grooming capability (that is from multi-hop grooming to a single-hop grooming). So that the purposes of the studying the impact of business dredge and business bypass on network energy optimization is reached. Optical layer , respectively , TDM and IP layers is added the following route constraints, and the network layer parameters ω (a binary number 3) is used to indicate whether start to use these three routing constraints. There will be seven kinds of meaningful combinations obtained; the meaning of each combination is shown in Table1. The experimental parameters η is valued 20%, the seven kinds of above combinations were done simulation respectively, the experiment results shown in Figure 4.

Table 1. The Parameters and Meanings of Network Layer

The value of parameter ω	Meanings
0(000)	Three network layers has the ability of business switching, that is IP over TDM
4(100)	The switching ability of optical layer is forbidden, that is IP over TDM network
2(010)	The switching ability of TDM layer is forbidden, that is IP over WDM network

1(001)	The switching ability of IP layer is forbidden, that is TDM over WDM network
3(011)	Only optical layer has the switching ability, which is optical network
5(101)	Only TDM layer has the switching ability, which is TDM network
6(110)	Only IP layer has the switching ability, which is IP network




Figure 4. The network power consumption optimization result of different network layer

(1) The impact of traffic grooming and bypass energy optimization. When network traffic is low, the traffic grooming can aggregate business into a small number of link transmission, reducing the active interface line cards and chassis number, so traffic grooming play a dominant role on the network energy consumption optimization. However, because the power consumption of the optical layer is much smaller than the IP layer WDM layer, for optical layer, the energy-saving effect of traffic grooming purposes is very limited, so the power consumption optimization of electrical switching network ($\omega = 5,6$) is better than the optical network ($\omega = 3$), the effect of two layer networks of pure electric exchange ($\omega = 4$) is better than the optical hybrid network ($\omega = 1,2$). When the volume of business is high, the effect of the traffic dredge on energy consumption optimization reduces. Traffic bypass play a leading role, as the optical network can achieve the business exchange at the wavelength of optical domain, and it has much lower power than the electric exchange, therefore the effect of the optical network ($\omega = 3$) is better than the electrical switching network ($\omega = 5,6$), the two layer networks of opto-electric hybrid ($\omega = 1,2$) is better than two layer networks of pure electric switching ($\omega = 4$).

(2) The impact of the network layer on energy consumption optimization. Different combinations of the network layer have different power optimization results. As Figure 4 shown, the three-layer networks 4 ($\omega = 0$) is better than the two-layer networks ($\omega = 1,2,4$), two-layer networks is better single network ($\omega = 3,5,6$), the maximum power consumption difference between different network layer combination is up to 30 %. Compared with two networks ($\omega = 1,2$), the advantage of three-layer network

power optimization effects is not clear, The mixed two-layer network of photoelectricity can be a good to have the dredge effect and bypass effect of optical switching effect, additional TDM-layer does not improve the network energy optimization almost, and the energy optimization solution time of 3 -layer network is much longer than the two-layer network. Therefore, considering from the aspects of network power optimization effect and solving time, I Pover WDM network is an ideal core network technology.

3.1.2. Dynamic power consumption and multi-layer network

Three -layer network (ie, $\omega = 0$) is used to get different values respectively from the dynamic power parameter η , (values were 0 %, 20 %, 40 % ... 100%) to do simulate experiments, the results shown in Figure 5, 6. The results show that the greater dynamic power consumption of network equipment is, the better network energy consumption optimization is, specifically in the following two aspects. First, when the volume of business is same, the dynamic power consumption is greater, the power consumption of the network is lower, when the dynamic power consumption grew from 0% to 100%, the network power consumption reduce averagely 10118W (see Figure 5). Secondly, the greater the dynamic power consumption of network equipment is, the network power consumption proportion in the largest networks during business low peak is smaller (see Figure 6) .




Figure 5. The affect that network equipment dynamic power on energy consumption optimization




Figure 6. The impact of network equipment dynamic power consumption on network power during business low peak period

3.1.3. The modular structure and the network power consumption

The modular design of the network devices will influence the network power consumption optimization. Different network equipment design, the functions on liner card and the machine frame is different, the results lead to the proportion of power between them is not the same. The modular parameter ζ is used to represent the percentage of chassis power consumption p_c in chassis and line card power $p_c + p_l$ percentage, that $\zeta = p_c / (p_c + p_l)$. The dynamic power consumption parameters η is 20%, parameter ζ values 0% , 20% , ... 100% , the simulation results shown in Figure 7 .




Figure 7. The effect modular of network device structure on energy consumption optimization

The results showed that the smaller the proportion of chassis –power is, the network energy optimization is better, the network consumes less power. When the business needs of the network is small, the effect of network device modular structure on network energy optimization is bigger (maximum up to 13461W). With the increasing demand of service, this effect becomes smaller, and there is a demand for some business value to make the effect reach a minimum value (influence is not more than 2399W). After analysis of the optimal solution, it can be found: t, the conditions to make the effect to be minimal is that: the amount of each node interfaces in network and the use of line cards (ie, the number which is in active state) are very close to the interface and line card chassis with the active state on amount (i.e., the number of equipped one).

It is easy to understand, when traffic is low, there are less amount of the interface and line card chassis to share the power of machine frame, while when the proportion of the machine frame power consumption reduce, the original part power of the chassis transferred to the line cards, and a large number of line cards in sleep, so the network power consumption can be reduced. When the previous minimum conditions is meet, all of the line cards and

interface in the active chassis almost are working, and thus the affect of the chassis power consumption proportion on the network has reached minimal. The current average link utilization of core network is low, network equipment with excellent modular design will help to optimize the network power consumption and reduce the energy consumption in network.

4. Conclusion

The traffic multistage grooming and bypass, the route of energy aware and varieties of energy-saving were discussed and the power consumption optimization model of multi-layer network with an IP layer, TDM layer and optical layers is established in this article. According to the specification parameters of actual network equipment to explore how different combinations of network layer, dynamic power dissipation dynamic power of network equipment and modular structure impact on energy optimization of multi-layer network by corresponding experiments. Experimental results show that: The power consumption of the network can be effectively reduced and the network power consumption of service off-peak can be reduced to 24% to 38 % of the service peak period by using this model.

References

- [1] Li Wan, Jie Yang. Advanced Split BIRCH Algorithm in Reconfigurable Network. *Journal of Networks*, Vol 8, No 9 (2013), 2050-2056
- [2] H. Z. Guo, Q. C. Chen, C. Xin, et al. "A Length-variable Feature Code Based Fuzzy Duplicates Elimination Approach for Large Scale Chinese WebPages", *Journal of Software*, 2012, 7(11), pp.262-269
- [3] K. Atual, J. Weissman, "ViDeDup: An Application-Aware Framework for Video De-duplication", In Proc. of the 3rd USENIX conference on Hot topics in storage and file systems, 2011, pp.7-7
- [4] Xiao-bo Li, Quan Zhou, "A lossless data hiding transmission method for satellite remote sensing image based on histogram modification," *Journal of Astronautics*, vol.34, no.5, pp. 686- 692, May,2013.
- [5] SHENG L, GANG W, STONES DS, et al. T-code: 3 Erasure Longest Lowest-Density MDS Codes . *IEEE Journal on Selected Areas in Communications*, 2010, 28(2):289-296.
- [6] N. P. Ramaiah, "De-duplication of Photograph Images Using Histogram Refinement", *Recent Advances in Intelligent Computational Systems*, 2011, pp.391-395
- [7] A. V. Sreedhanya and K. P. Soman, "Secrecy of cryptography with compressed sensing," *International Conference on Advances in Computing and Communications*, pp. 207-210, 2012.
- [8] C. Wengert, M. Douze, H. Jegou. "Bag-of-colors for Improved Image Search", In Proc. of the 19th ACM international conference on Multimedia, 2011, pp.1437-1440
- [9] CHEN T W., SHEN G W., XU B H., et al.H-Code : A Hybrid MDS Array Code to Optimize Partial Stripe Writes in RAID-6.// *Proceedings of the 2011 IEEE International Parallel & Distributed Processing Symposium*, Anchorage, Alaska, USA, IEEE Press,2011:782-793.
- [10] J.Tian, "Reversible watermarking using a difference expansion," *IEEE Trans. Circuits Syst. Video Technol.*, vol. 13, no. 8, pp. 890-896, Aug.2003.
- [11] L. An, X. Gao, C. Deng, and F. Ji, "Reversible watermarking based on statistical quantity histogram," in Proc. Adv. Multimedia Inform. Process. LNCS 5879. 2009, pp. 1300-1305.
- [12] FENG G.-L., DENG R., BAO F., SHEN J.-C.. New Efficient MDS Array Codes for RAID, Part I: Reed Solomon Like Codes for Tolerating Three Disk Failures. *IEEE Trans. Computers*, 2005,54(9): 1071-1080.
- [13] X. Zhang, Y. Ren, G. Feng and Z. Qian, "Compressing encrypted image using compressive sensing," 2011 7th International Conference on Intelligent Information Hiding and Multimedias Signal Processing (IIH-MSP), pp. 222-225, 2011.
- [14] XIANG H L, JI W S. Summary of Research for Erasure Code in Storage System. *Journal of Compute Research and Development*,2012, 49(1) : 1-11.
- [15] P. Lu, Z. Xu, X. Lu and X. Liu, "Digital image information encryption based on Compressive Sensing and double random-phase encoding technique," *Optik-International Journal for Light and Electron Optics*, vol. 124, pp. 2514-2518, 2013.
- [16] J. He, Y. Geng and K. Pahlavan, Modeling Indoor TOA Ranging Error for Body Mounted Sensors, 2012 IEEE 23rd International Symposium on Personal Indoor and Mobile Radio Communications (PIMRC), Sydney, Australia Sep. 2012 (page 682-686)
- [17] Y. Geng, J. Chen, K. Pahlavan, Motion detection using RF signals for the first responder in emergency operations: A PHASER project[C], 2013 IEEE 24nd International Symposium on Personal Indoor and Mobile Radio Communications (PIMRC), London,Britain Sep. 2013
- [18] S. Li, Y. Geng, J. He, K. Pahlavan,Analysis of Three-dimensional Maximum Likelihood Algorithm for Capsule Endoscopy Localization, 2012 5th International Conference on Biomedical Engineering and Informatics (BMEI), Chongqing, China Oct. 2012 (page 721-725).
- [19] Y. Geng, J. He, H. Deng and K. Pahlavan, Modeling the Effect of Human Body on TOA Ranging for Indoor Human Tracking with Wrist Mounted Sensor, 16th International Symposium on Wireless Personal Multimedia Communications (WPMC), Atlantic City, NJ, Jun. 2013.
- [20] Y. Geng, J. He, K. Pahlavan, Modeling the Effect of Human Body on TOA Based Indoor Human Tracking[J], *International Journal of Wireless Information Networks* 20(4), 306-317